

STANDARD INCLUSIONS

EXTERNAL

Base Floor

Concrete slab using waffle pod 325 mm high OR Steel bearers and joists, with yellow tongue flooring and posts on concrete piers

Termite Control

SLAB: Perimeter Termite Reticulation System- with slow releasing deterrant OR BEARERS & JOISTS: Exposed Steel Bearers and Joist act as visual point of annual inspection by owner

Wall, Ceiling & Roof Framing

Timber framing, to AS1684, including 90mm timber studs spaced at 450mm intervals MGP10 High Grade or H2F5 Termite Treated Pine

(Other Companies 70mm pine studs @ 600mm spacing) Wall framing at 2450mm high, includes external sarking

Roofing

Boral concrete roof tiles at 20 degrees including sarking

Eaves & Verges

300mm eaves with fibre cement lining, Colorbond fascia and quad guttering

Insulation

R2 batts to external walls R3.5 batts to ceiling

Windows

5 x Powdercoated aluminium sliding windows, with security locks and flyscreens. 1 sliding door with security screen (Price includes Black, White, Primrose and Silver Only- all other colours additional cost)

External Walls

James Hardie Primeline – Chamfer Profile

Downpipes

Colourbond Downpipes, 3 Included

Entry Doors

Solid core 820 entry doors from builder's range with glass panel and weather strip

Metering

Electricity Meter (basic allowance \$500 – Subject to quote by Electrician) Water flow reader(measures usage between main dwelling & granny flat)

Others

Full and final clean inside granny flat and around external 6 years Home Owners Warranty Public Liability and Builders All Risk Insurance.

\$112,200 incl GST

2 Bedroom, 60m2 Granny Flat

INCLUDES

DESIGN & APPROVAL

(Assuming land is fairly level, no other land issues and a standard design is selected)

WIDE RANGE OF UPGRADES AVAILABLE

INTERNAL

Waterproofing

PVC Sheet Membranes (flexible membrane system)

Wall & Ceiling Linings

10mm plasterboard to all internal walls & ceiling Villaboard lining to bathroom 90mm coved cornices throughout

Wardrobes

Mirrored or plain sliding doors with melamine shelves & drawers

Joinery

Skirtings-66x11mm - half splay profile Architrave- 66x11mm - half splay profile Hollow core internal doors including all door furniture, from builders standard range

Floor Coverings

450 x 450mm tiles to bathroom 450 x 450mm tiles to kitchen, living & dining area. Bedrooms either carpet or floating laminate floors

Painting

Internal: walls, ceilings, doors, skirtings & architraves. External: eaves, door and external walls (also downpipes if charged line)

Separate Laundry

Clark 35L tub with cabinet and mixer, Tiled floor & skirting Tiled splashback behind tub. Hot & cold taps for washing machine Fan/light and power point.

Kitchen

Sprayed Polyurethane doors and panels (any colour of your choice) 7m cabinets includes upper, lower and overhead fridge cabinets 600mm full length pantry with microwave space

Laminate benchtop, Tiled splashback -includes 300 x 600 options Westinghouse oven and ceramic cooktop (Gas cooktops where available) Euromaid slide out rangehood, Clark 1 3/4 bowl sink with 'gooseneck' mixer

Bathroom

1200mm high wall tiling to perimeter, including 300 x 600 tile options 2100mm high wall tiling in shower

Stylus Banksia back to wall dual flush wc

750mm Polyurethane vanity with stone top, drop in basin & mirror over Look vanity and shower mixers Look towel rail & toilet roll holder

Framed shower screen

Light fan and heater combination

Hot Water System

Bottled Gas LPG Infinity Hot Water System including automatic diverter for gas Bottles OR Electric Heat Pump 170L hot water System- Note:Granny Flats Australia Owns Rebates

Electrical Hard wired smoke detector

Internal distribution board Controlling all internal power 10 x usable double power points throughout – includes 1 external Additional 4 hidden power points for appliances 9 x LED downlights throughout

- 1 x External Sensor Light with double globe
- 1 x Aerial Point For TV Including external Digital Aerial
- 1 x Internal phone point

Standard Connection of Services

Electricity is connected to meter box up to 15m Connection to sewer up to 15m Connection to existing stormwater system up to 15m Conduit for data line